

Claims

What is claimed and desired to be secured by Letters Patent is:

18. A warning sign comprising first and second parts pivotably interconnected at their in use upper ends and pivotable between a first storage position in which the first and second parts are arranged in side-by-side relationship and a second operative position in which the first and second parts are at an angle to one another, detent means for releasably retaining the first and second parts in the second operative position, and a third part releasably supportable by the detent means.
19. A warning sign as claimed in claim 18, wherein the two parts have ground contacting foot portions at their in use lower ends, so that, with said foot portion or portions of one part spaced from said foot portion or portions of the other part, the sign will be self-supporting on the ground.
20. A warning sign as claimed in claim 18, wherein the detent means comprises at least one projection and at least one corresponding aperture or recess, the projection being arranged to fit in the aperture or recess as a snap or friction fit when the first and second parts are in the second operative position.
21. A warning sign as claimed in claim 20, wherein the first and second parts each have one said projection which cooperates with one said corresponding aperture or recess formed in the other part.

- 1 22. A warning sign as claimed in claim 20, wherein the third part includes
2 a support portion having one or more openings dimensioned to
3 receive a corresponding said projection therethrough.
- 4 23. A warning sign as claimed in claim 22, wherein the or each opening
5 in the third part is a through-hole.
- 6 24. A warning sign as claimed in claim 22, wherein the said projection can
7 only be inserted into the corresponding opening of the third part when
8 the first and second parts are in the first storage position.
- 9 25. A warning sign as claimed in claim 22, wherein the said projection can
10 only be removed from the corresponding opening of the third part
11 when the detent means is released.
- 12 26. A warning sign as claimed in claim 22, wherein the or each opening
13 in the third part is a recess formed in an edge of the third part.
- 14 27. A warning sign as claimed in claim 22, wherein at least one said
15 recess is keyhole shaped so as to snap-fit engageable with the said
16 projection of the detent means.
- 17 28. A warning sign as claimed in claim 26, wherein the third part, in use,
18 is engageable with and disengageable from the projection of the
19 detent means, when the first and second parts are in the first storage
20 position and the second operative position.
- 21 29. A warning sign as claimed in claim 18, further comprising a fourth
22 display part releasably engageable with the third part.
- 23

- 1 30. A warning sign as claimed in claim 29, wherein the third part includes
2 an elongate channel in which the bottom end of the fourth display part
3 is receivable.
- 4 31. A warning sign as claimed in claim 29, wherein the third part
5 comprises two members, each member including an elongate channel
6 in which a side of the fourth display part is, at least in part, receivable.
- 7 32. A warning sign as claimed in claim 29, wherein the third part includes
8 a transparent holder for holding the fourth display part.
- 9 33. A warning sign as claimed in claim 32, wherein the transparent holder
10 is a sleeve into which the fourth display part can be slidably inserted.

11